



BEARING DRIVESHAFT ANDERSON, INC.

3RSR3N+[20-220/1]LM THK Miniature Linear Guide Full Ball RSR Series

Bearing No. 3RSR3N+[20-220/1]LM

Days to Ship	45 Days
Block Type	[Long] N: Long
The number of LM blocks combined with a axis	3
Nominal Part Number	3
Rail Type	Standard
Rail Width W1	3 mm
Mounting Height M	4 mm
Rail Length L	20 ~ 220 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	300
Basic Load Rating Static Rating Co(N)	440
Allowable Static Moment MA(N m)	0.726
Allowable Static Moment MB(N m)	0.726
Allowable Static Moment MC(N m)	0.73
Symbols for Dust Resistance	None
Block external dimension W	8 mm
Block external dimension L	16 mm
Number of Block Mounting	2

3RSR3N+[20-220/1]LM Bearing 2D drawings and 3D CAD models



BEARING DRIVESHAFT ANDERSON, INC.

Holes(holes)	
Mounting Hole Dimension S(M)	M2
Mounting Hole Screw Depth	1.3 mm
Block dimension L1	10.7 mm