



BEARING DRIVESHAFT ANDERSON, INC.

SR35W1UUM(GK) THK Radial Linear Guide (Block Only) Interchangeable SR Series

Bearing No. SR35W1UUM(GK)

Days to Ship	4 Days
RoHS	10
Block Type	[Standard] W: Standard
Nominal Part Number	35
Rail Type	Standard
Mounting Height M	48 mm
Material	Stainless Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	41700
Basic Load Rating Static Rating Co(N)	77200
Allowable Static Moment MA(N m)	740
Allowable Static Moment MB(N m)	454
Allowable Static Moment MC(N m)	1010
Block Mounting Hole Pitch (Width Direction)	50 mm
Block Mounting Hole Pitch (Length Direction)	50 mm
Block Mounting Hole Diameter	8
Rail Mounting Hole Pitch	80 mm
Rail Mounting Hole Diameter	9

SR35W1UUM(GK) Bearing 2D drawings and 3D CAD models



BEARING DRIVESHAFT ANDERSON, INC.

Symbols for Dust Resistance	UU: End seals
Block external dimension W	70 mm
Block external dimension L	111 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M8
Mounting Hole Screw Depth	12 mm
Block dimension L1	79 mm