





BEARING DRIVESHAFT ANDERSON, INC.



Cylindrical bore



Tapered bore



10 mm x 30 mm x 9 mm SKF 1200ETN9 Self aligning ball bearings

Bearing No. 1200ETN9

1200ETN9 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|-------------|
| Size | 10x30x9 mm |
| Bore Diameter | 10 mm |
| Outer Diameter | 30 mm |
| Width | 9 mm |
| d | 10 mm |
| D | 30 mm |
| B | 9 mm |
| C | 9 mm |
| d2 | 16,7 mm |
| r1 min. | 0,6 mm |
| r2 min. | 0,6 mm |
| D1 | 24,4 mm |
| da min. | 14,2 mm |
| Da max. | 25,8 mm |
| ra max. | 0,6 mm |
| Weight | 0,034 Kg |
| Basic dynamic load rating (C) | 5,53 kN |
| Basic static load rating (C0) | 1,18 kN |
| Fatigue load limit (Pu) | 0,061 |
| Reference speed | 56000 r/min |
| Limiting speed | 36000 r/min |
| Calculation factor (e) | 0,33 |
| Calculation factor (kr) | 0,04 |
| Calculation factor (Y0) | 2 |
| Calculation factor (Y1) | 1,9 |



BEARING DRIVESHAFT ANDERSON, INC.